



2115TiMAX Impact Wrench

- Titanium hammer case and composite housing
- 7-vane motor delivers added power with less weight
- Finely tuned twin hammer impact mechanism and motor deliver more torque, durability, and efficiency
- Feather-touch trigger provides maximum control
- Max. Torque in Reverse: 300 ft-lbs.
- Drive Type: Square Hog-Ring



Ingersoll Rand.

Model No.	Mfg. No.	Air Consumption	Air Inlet	Sound Level (dBA)	Drive"	No Load RPM	Price /Each
BW352	2115TiMAX	4 CFM	1/4" NPTF	107.6	3/8	15000	

Ultra-Compact Air Impact Wrench

- Stubby 4.6" length and compact design gives you total control to get up, under, over, or around any tough job
- One-handed forward/reverse push button and 3-mode power regulator give you maximum control
- Drive Type: Square, Hog-Ring
- Nut-Busting Torque: 475 ft-lbs
- Blows Per Minute: 1350



Ingersoll Rand.

Model No.	Mfg. No.	Air Consumption	Air Inlet	Sound Level (dBA)	Drive"	No Load RPM	Price /Each
UAI480	15QMAX	17 CFM	1/4" NPTF	89.7	3/8	6000	

2235TiMAX Impact Wrench

- The high torque output of the powerful vane motor is optimized to increase safety and control over the tool
- Titanium hammer case is designed to be strong and durable
- Features patented quiet tool technology reducing sound levels
- Max. Torque in Reverse: 930 ft-lbs.
- Drive Type: Square Hog-Ring



Ingersoll Rand.

Model No.	Mfg. No.	Air Consumption	Air Inlet	Sound Level (dBA)	Drive"	No Load RPM	Price /Each
NKD054	2235TiMAX	6 CFM	1/4" NPTF	109	1/2	8500	

2135QXPA Impact Wrench

- Light, quiet, and powerful design
- Drive Type: Square
- Max. Torque in Reverse: 780 ft-lbs.
- Torque (Forward): 700 ft-lbs.
- Torque (Reverse): 780 ft-lbs.



Ingersoll Rand.

Model No.	Mfg. No.	Air Consumption	Air Inlet	Sound Level (dBA)	Drive"	No Load RPM	Price /Each
UAE021	2135QXPA	5 CFM	1/4" NPTF	90.7	1/2	11000	

2145QiMAX Impact Wrench

- Titanium hammer case is designed to be strong and durable
- Finely tuned twin hammer impact mechanism and motor deliver more torque, durability, and efficiency
- Feather-touch trigger provides maximum control
- Max. Torque in Reverse: 1350 ft-lbs.
- Drive Type: Square Hog-Ring and Thru-Hole



Ingersoll Rand.

Model No.	Mfg. No.	Air Consumption	Air Inlet	Sound Level (dBA)	Drive"	No Load RPM	Price /Each
NJT321	2145QiMAX	8.5 CFM	3/8" NPT	107.3	3/4	7000	

2925 Series Impact Wrench

- Bronze endplates and a corrosion preventative treatment prevents internal rust in outdoor, wet environments
- Choice of reverse bias or non-biased motors gives you solutions for both removing or fastening bolts
- Pressure-fed mechanism lubrication ensures complete coverage throughout the tool
- Weight: 12.2 lbs.
- Length: 9"
- Configuration: Pistol
- Free Speed Sound Level Pressure: 99.6



Ingersoll Rand.

Model No.	Mfg. No.	Air Consumption	Air Inlet	Sound Level (dBA)	Drive"	No Load RPM	Price /Each
UAE347	2925RBP3TI	60	3/8" NPT	110.6	1	5200	

3900 Series Impact Wrenches

- Thanks to the bronze end-plate and a corrosion preventative treatment, this series is corrosion and wear resistant, making it great for outdoor conditions
- The titanium hammer case and metal housing means this tool can withstand even the harshest conditions
- Twin hammer mechanism ensure consistent power and balance



UAE353



UAE350



Ingersoll Rand.

Model No.	Mfg. No.	Air Consumption	Air Inlet	Sound Level (dBA)	Drive	No Load RPM	Forward Torque	Blows Per Minute	Weight lbs.	Length"	Price /Each
UAE350	3940B2TI	64	1/2" NPT	114.4	1"	6000	1650 ft-lbs.	800	21.2	13.5	
UAE353	3955B2TI	80	1/2" NPT	112.5	1-1/2"	2750	3900 ft-lbs.	700	34.6	16.5	