



Utility Hammers

- Ideal for structural maintenance and repair
- Air Consumption: 25 CFM
- Air Inlet: 1/4" NPTF
- Sound Level (dBA): 100



UAG272



UAG273

AURORA TOOLS

Model No.	BPM	Bore & Stroke	Cold Rivet Capacity	Head Material	Overall Length	Chisel Shank	Bore Diameter	Price /Each
UAG272	3000	3/4" x 2-5/8" (19.0mm x 66.0mm)	1/4" (6.4 mm)	Steel	7-1/2" (190 mm)	0.401" (Round)	3/4" ID (19.05 mm)	
UAG273	2200	3/4" x 3-5/8" (19.0mm x 92.0mm)	5/16" (7.9 mm)	Steel	9-13/16" (250 mm)	0.401" (Round)	3/4" ID (19.05 mm)	

Heavy-Duty Air Riveter

- 90 PSI air pressure recommended for maximum performance
- Powerful pulling load of 1940 lbs.
- Can be used on all rivet material types, including steel and aluminum, up to 3/16"
- 9/16" stroke sets rivets in one hit, increasing efficiency
- Very compact and lightweight – only 3.2 lbs.
- High quality, see-through collection bottle
- Air relief valve prevents overloading for greater tool service life
- Designed for professional automotive and

light- to medium-duty industrial applications

- Rivet Size: 3/32" - 3/16"
- Air Inlet: 1/4"
- Average Air Consumption: 4 CFM
- Min. Hose Size: 3/8"
- Includes:
 - Air Riveter,
 - 3/32" (2.4 mm) Nosepiece,
 - 1/8" (3.2 mm) Nosepiece,
 - 5/32" (4.0 mm) Nosepiece,
 - 3/16" (4.8 mm) Nosepiece

Model No. UAV953
 Mfg. No. 409005
 Price/Each \$



EXCEEDING EXPECTATIONS

