



Easyflex Premium Air Hoses w/Fittings

- Technopolymer engineered to be tough and ultra-flexible at extremely low temperatures
- Easily re-coiled after use, no memory
- Lightweight
- -65°F to 149°F, 300 PSI
- Rubber guard bend restrictors on hose assemblies to extend the life of the hose
- Colour: Yellow or blue



TOPRING

Model No.	Mfg. No.	Colour	Hose I.D."	Hose Length'	Fittings (M)NPT	Price /Each
TLZ735	72.164	Yellow	1/4	25	1/4	
TLZ736	72.168	Yellow	1/4	50	1/4	
TLZ737	72.170	Yellow	1/4	100	1/4	
TLZ738	72.364	Yellow	3/8	25	1/4	
TLZ739	72.368	Yellow	3/8	50	1/4	
TLZ740	72.370	Blue	3/8	100	1/4	

Maxpro Self-Storing Nylon Air Hoses w/Fittings

- Self-storing
- Excellent abrasion resistance
- Swivel fittings allow maximum directional flexibility
- Reusable and repairable fittings
- -40°F to 180°F, up to 200 PSI
- Colour: Red

TA181



TOPRING

Model No.	Mfg. No.	Hose I.D."	Hose Length'	Fittings (M)NPT	Price /Each
TA181	11.421	1/4	12,5	1/4	
TA182	11.441	1/4	25	1/4	
TA185	11.641	3/8	25	3/8	
TA187	11.681	3/8	50	3/8	

REPLACEMENT SWIVEL FITTINGS

Model No.	Mfg. No.	Hose I.D."	Hose Length'	Fittings (M)NPT	Price /Each
TS332	11.042	1/4	-	1/4	
TS334	11.062	3/8	-	3/8	
TS335	11.065	3/8	-	1/4	

Flexhybrid Air Hoses w/Fittings

- Engineered hybrid polymer combining best features from PVC and rubber
- Superior flexibility, lightweight and economical
- 14°F to 140°F, 300 PSI
- Good resistance to oils, heat, ozone and abrasion
- Colour: Red

TNB036



TOPRING

Model No.	Mfg. No.	Hose I.D."	Hose Length'	Fittings (M)NPT	Price /Each
TNB036	70.115	1/4	25	1/4	
TNB037	70.119	1/4	50	1/4	
BC368	70.316	3/8	25	1/4	
BC370	70.318	3/8	50	1/4	
BC376	70.415	1/2	25	3/8	
BC380	70.419	1/2	50	3/8	

Airflex Premium Air Hoses w/Fittings

- Excellent abrasion resistance
- Medium oil resistance
- -40°F to 212°F, 250 PSI
- Quality general purpose rubber air hose
- Colour: Red

BU260



TOPRING

Model No.	Mfg. No.	Hose I.D."	Hose Length'	Fittings (M)NPT	Price /Each
BU260	71.114	1/4	25	1/4	
UP477	71.118	1/4	50	1/4	
BU282*	71.315	3/8	25	1/4	
BU286*	71.319	3/8	50	1/4	
BU285*	71.318	3/8	50	3/8	
BU306	71.419	1/2	50	3/8	
BU305	71.418	1/2	50	1/2	

*Rubber guard bend restrictors to increase the life of air hose

Topflex Rubber Air Hoses

- Maximum oil and heat resistance
- Spark resistant
- Reusable fittings – no crimping required
- -40°F to 212°F, 300 PSI
- Synthetic rubber cover
- Colour: Black



TA511



TNB038

TOPRING

Model No.	Mfg. No.	Hose I.D."	Hose Length'	Fittings (M)NPT	Price /Each
TNB038	77.125	1/4	25	1/4	

TOPFLEX LOCK-ON AIR HOSES

Model No.	Mfg. No.	Hose I.D."	Hose Length'	Fittings (M)NPT	Price /Each
TNB039	77.128	1/4	50	1/4	
TNB040	77.130	1/4	100	1/4	
BU472	77.348	3/8	50	1/4	
TNB042	77.338	3/8	50	3/8	
TNB043	77.110	1/4	500	-	
TNB044	77.310	3/8	500	-	

REPLACEMENT REUSABLE FITTINGS

Model No.	Mfg. No.	Hose I.D."	Hose Length'	Fittings (M)NPT	Price /Each
TA511	41.861	1/4	-	1/4	
TA512	41.862	3/8	-	1/4	
TA526	41.880	1/4	-	Barb joint	
TA527	41.881	3/8	-	Barb joint	

Flexcoil Self-Storing Polyurethane Air Hoses w/Fittings

- Offers little resistance to pull and automatically recoils
- Swivel fittings allow maximum directional flexibility
- Reusable and repairable fittings
- -40°F to 158°F, 140 PSI
- Colour: Red

TA216



TOPRING

Model No.	Mfg. No.	Hose I.D."	Hose Length'	Fittings (M)NPT	Price /Each
TA216	17.610	1/4	15	1/4	
TA217	17.615	1/4	20	1/4	
TA218	17.620	1/4	25	1/4	
TA219	17.625	1/4	30	1/4	
TA220	17.650	1/4	50	1/4	
TA226	17.710	3/8	15	3/8	
TA227	17.714	3/8	15	1/4	
TA230	17.720	3/8	25	3/8	
TA231	17.724	3/8	25	1/4	