

Hose Reel

- Heavy-duty, reinforced steel stampings for increased strength
- For use with air and water
- Compact design allows reels to fit in tight locations
- Multi-position guide arms for multiple mounting options
- Kinkless, oil resistant high quality hose
- Spring rewind features long life spring with declutching arbor
- Durable, corrosion-resistant powder coat paint
- **FPDM Rubber**



Model	Inner Hose	Hose	Working	Hose	Dimensions					Reel	
No.	Diameter"	Length'	Pressure	End	W"	X	D"	X	H"	Outlet	Inlet
UAV178	1/4	35	300 PSI	3/8" NPT	17-1/3	χ	15	Х	8-1/3	1/4" NPT	3/8" NPT
UAV179	3/8	25	300 PSI	3/8" NPT	17-1/3	X	15	X	8-1/3	1/4" NPT	3/8" NPT
UAV180	3/8	35	300 PSI	3/8" NPT	17-1/3	Х	15	Х	8-1/3	1/4" NPT	3/8" NPT
UAV181	3/8	50	300 PSI	3/8" NPT	18-7/10	Х	17-1/2	Х	8-1/2	1/4" NPT	3/8" NPT
UAV182	1/2	50	300 PSI	1/2" NPT	21-7/10	Х	18-1/2	Х	9-2/3	1/2" NPT	1/2" NPT



Welding Hose Reel

- Heavy-duty, reinforced steel stampings for increased strength
- Compact design allows reels to fit in tight locations
- Multi-position guide arms for multiple mounting options
- Kinkless, oil resistant high quality hose
- Spring rewind features long life spring with declutching arbor
- Durable, corrosion-resistant powder coat paint
- 1/4" oxygen and acetylene twin hose
- Leakproof double O-ring seals
- Grade R hose



Model	Inner Hose	Hose	Working	Hose	Dimensions				Reel			
No.	Diameter"	Length'	Pressure	End	W"	X	D"	X	H"	Outlet	Inlet	/Each
UAV183	1/4	25	300 PSI	9/16" NPTF	17-1/3	χ	15	Х	8-1/3	1/4" NPT	9/16" NPTF	
UAV184	1/4	50	300 PSI	9/16" NPTF	18-7/10	X	17-1/2	X	8-1/2	1/4" NPT	9/16" NPTF	



Liahtweiaht	&	Economical	Industrial	Reels
9	•			

- Lighter spring driven hose reel designed for applications that are less demanding, yet require a product that can withstand industrial use
- Steel components are individually powder coated and teamed with composite materials, which virtually eliminates corrosion
- Lightweight for air or water designed for less demanding applications yet can withstand industrial use - sold with hose

_	
•	DEEL CRAET
X -	NEELUNAF I

Model No.	Mfg. No.	Drive Type	Hose I.D."	Hose Length'	Max PSI	Hose Outlet (M) NPT"	Reel Inlet (F) NPT"	Reel Outlet (F) NPT"	W"	D X	imension D"	is X	Н"	Wt. Ibs.	Prio /Eac
STEEL	& COMPO	SITE REE	LS												
FH522	RT435-OLP	Spring	1/4	35	300	1/4	3/8	-	5 3/4	Х	16 1/2	Х	17 7/8	20	
FH523	RT450-OLP	Spring	1/4	50	300	1/4	3/8	-	5 3/4	Х	16 1/2	Х	17 7/8	24	
FH524	RT635-OLP	Spring	3/8	35	300	1/4	3/8	-	5 3/4	Х	16 1/2	Х	17 7/8	21	
FH525	RT650-OLP	Spring	3/8	50	300	1/4	1/2	-	6 1/4	Х	16 1/2	Х	17 7/8	27	
F1056	RT835-OLP	Spring	1/2	35	300	1/2	1/2	-	6 1/4	Х	16 1/2	Х	17 7/8	27	
F1057	RT850-OLP	Spring	1/2	50	300	1/2	1/2	-	7 3/4	Х	16 1/2	Х	17 7/8	37	



UAV184

FH522

2-Year Limited Warranty Standard colour as shown - black composite/powder coat paint red base & guide arm

Retractable Air & Water Hose Reel

- Ideal for indoor shop and industrial applications
- Made from premium quality impact-resistant polypropylene materials
- Positive latching mechanism locks hose at desired length
- Hybrid polymer hose helps eliminate kinks
- Features a 180-degree integrated wall and overhead swivel bracket
- Hose Length: 50'
- Working Pressure: 300 psi
- Inlet: 3/8" NPT
- Includes: 36" Inlet Hose
- Material: Polypropylene
- Max. Temperature: 100°C (210°F)
- Min. Temperature: -10°C (14°F)

Model No. UAV844 Mfg. No. 028283 Price/Each \$





