



Quick Couplers

High performance, corrosion resistant quick couplers built to interchange with industrial type couplings. Offer a higher flow for maximum on-line performance of hand-held air tools. Heavy-duty, high quality design.

Industrial Plug
TA249



Industrial Automax
Automatic Coupler
TZ184



Industrial Maxquik
Manual Coupler
TA268



Industrial Automax
Automatic Coupler
TZ228



TOPRING

1/4 INDUSTRIAL INTERCHANGE

1/4 INDUSTRIAL PLUGS

- Zinc Plated or Stainless Steel 304
- Corrosion resistant

1/4 INDUSTRIAL AUTOMAX COUPLERS

- Automatic push-to-connect operation
- Proven and positive connection using pin-lock mechanism
- Max 250 PSI
- 37 SCFM

1/4 INDUSTRIAL MAXQUIK COUPLERS

- Manual operation
- Sleeve guard prevents accidental disconnection
- Max 250 PSI
- 24 SCFM

| Size" | Model No. | Mfg. No. | Price/Each | Size" | Model No. | Mfg. No. | Price/Each | Size" | Model No. | Mfg. No. | Price/Each |
|------------------------------|-----------|----------|------------|------------------------|-----------|----------|------------|------------------------|-----------|----------|------------|
| FEMALE THREAD (F) NPT | | | | | | | | | | | |
| 1/8 | TA243 | 20.122 | - | 1/8 | - | - | - | 1/8 | - | - | - |
| 1/4 | TA244 | 20.142 | - | 1/4 | TZ184 | 20.444 | - | 1/4 | TA268 | 20.842 | - |
| 1/4 (Stainless) | TLV344 | 20.146 | - | 1/4 (Stainless) | - | - | - | 1/4 (Stainless) | - | - | - |
| 3/8 | TA245 | 20.162 | - | 3/8 | - | - | - | 3/8 | TA269 | 20.862 | - |
| MALE THREAD (M) NPT | | | | | | | | | | | |
| 1/8 | TA247 | 20.222 | - | 1/8 | - | - | - | 1/8 | - | - | - |
| 1/4 | TA248 | 20.242 | - | 1/4 | TZ185 | 20.644 | - | 1/4 | TA271 | 20.942 | - |
| 1/4 (w/thread sealant) | TLV345 | 20.248 | - | 1/4 (w/thread sealant) | - | - | - | 1/4 (w/thread sealant) | - | - | - |
| 1/4 (Stainless) | TLV346 | 20.246 | - | 1/4 (Stainless) | - | - | - | 1/4 (Stainless) | TLV348 | 20.946 | - |
| 3/8 | TA249 | 20.262 | - | 3/8 | TZ227 | 20.664 | - | 3/8 | TA272 | 20.962 | - |
| HOSE BARB | | | | | | | | | | | |
| 1/4 I.D. | TA252 | 20.342 | - | 1/4 I.D. | TZ228 | 20.744 | - | 1/4 I.D. | TA258 | 20.542 | - |
| 3/8 I.D. | TA254 | 20.362 | - | 3/8 I.D. | TZ230 | 20.764 | - | 3/8 I.D. | TA260 | 20.562 | - |

3/8 INDUSTRIAL INTERCHANGE

3/8 INDUSTRIAL PLUGS

- Zinc plated steel construction
- Corrosion resistant

3/8 INDUSTRIAL AUTOMAX COUPLERS

- Automatic push-to-connect operation
- Proven and positive connection using pin-lock mechanism
- Max 250 PSI
- 62 SCFM

3/8 INDUSTRIAL MAXQUIK COUPLERS

- Manual operation
- Sleeve guard prevents accidental disconnection
- Max 250 PSI
- 56 SCFM

| Size" | Model No. | Mfg. No. | Price/Each | Size" | Model No. | Mfg. No. | Price/Each | Size" | Model No. | Mfg. No. | Price/Each |
|------------------------------|-----------|----------|------------|----------|-----------|----------|------------|----------|-----------|----------|------------|
| FEMALE THREAD (F) NPT | | | | | | | | | | | |
| 1/4 | TA273 | 21.142 | - | 1/4 | TA281 | 21.442 | - | 1/4 | TZ144 | 21.842 | - |
| 3/8 | TA274 | 21.162 | - | 3/8 | TA282 | 21.462 | - | 3/8 | TZ145 | 21.862 | - |
| 1/2 | TZ132 | 21.182 | - | 1/2 | TZ137 | 21.482 | - | 1/2 | TZ146 | 21.882 | - |
| MALE THREAD (M) NPT | | | | | | | | | | | |
| 1/4 | TA278 | 21.242 | - | 1/4 | TZ138 | 21.642 | - | 1/4 | TZ147 | 21.942 | - |
| 3/8 | TA279 | 21.262 | - | 3/8 | TA283 | 21.662 | - | 3/8 | TZ148 | 21.962 | - |
| 1/2 | TZ133 | 21.282 | - | 1/2 | TZ139 | 21.682 | - | 1/2 | TZ149 | 21.982 | - |
| HOSE BARB | | | | | | | | | | | |
| 3/8 I.D. | TA280 | 21.362 | - | 3/8 I.D. | TZ142 | 21.762 | - | 3/8 I.D. | TZ152 | 21.562 | - |
| 1/2 I.D. | TZ136 | 21.382 | - | 1/2 I.D. | - | - | - | 1/2 I.D. | TZ153 | 21.582 | - |

1/2 INDUSTRIAL INTERCHANGE

1/2 INDUSTRIAL PLUGS

- Zinc plated steel construction
- Corrosion resistant

1/2 INDUSTRIAL AUTOMAX COUPLERS

- Automatic push-to-connect operation
- Proven and positive connection using pin-lock mechanism
- Max 250 PSI
- 99 SCFM

3/8 INDUSTRIAL MAXQUIK COUPLERS

- Manual operation
- Sleeve guard prevents accidental disconnection
- Max 250 PSI
- 75 SCFM

| Size" | Model No. | Mfg. No. | Price/Each | Size" | Model No. | Mfg. No. | Price/Each | Size" | Model No. | Mfg. No. | Price/Each |
|------------------------------|-----------|----------|------------|----------|-----------|----------|------------|----------|-----------|----------|------------|
| FEMALE THREAD (F) NPT | | | | | | | | | | | |
| 3/8 | TZ154 | 22.162 | - | 3/8 | - | - | - | 3/8 | - | - | - |
| 1/2 | TZ155 | 22.182 | - | 1/2 | TZ165 | 22.482 | - | 1/2 | TZ175 | 22.882 | - |
| 3/4 | TZ156 | 22.192 | - | 3/4 | - | - | - | 3/4 | TZ176 | 22.892 | - |
| MALE THREAD (M) NPT | | | | | | | | | | | |
| 3/8 | TZ158 | 22.262 | - | 3/8 | - | - | - | 3/8 | - | - | - |
| 1/2 | TZ159 | 22.282 | - | 1/2 | TZ169 | 22.682 | - | 1/2 | TZ179 | 22.982 | - |
| 3/4 | TZ160 | 22.292 | - | 3/4 | - | - | - | 3/4 | TZ180 | 22.992 | - |
| HOSE BARB | | | | | | | | | | | |
| 1/2 I.D. | TZ162 | 22.382 | - | 1/2 I.D. | - | - | - | 1/2 I.D. | - | - | - |