



Filters/Regulators & Lubricators (Gauge Included)

- High-flow capacity reduces costly pressure drop
- Compact size allows greater design flexibility
- Lightweight construction for ease of installation

TOPRING

Model No.	NPT Size"	Max SCFM @ 100 PSI	Max PSI	Reduced Pressure Range PSI	Max Temp. °F	Drain Type	Bowl Type	Bowl Cap. oz.	H"	W"	Price /Each
COMPACT MODULAR DESIGN, 5-MICROMETRES FILTRATION											
TA719	1/4	31	150	0-125	125	Manual	Polyurethane Plast	1.5	7 1/16	3 3/16	
TA720	1/4	31	150	0-125	125	Auto	Polyurethane Plast	1.5	7 1/16	3 3/16	
TA723	1/4	38	150	0-125	125	Manual	Polyurethane w/guard	3.8	8 1/16	4 23/64	
TA724	1/4	38	150	0-125	125	Auto	Polyurethane w/guard	3.8	8 1/16	4 23/64	
TA728	3/8	73	150	0-125	125	Auto	Polyurethane w/guard	3.8	8 1/16	4 23/64	
TA731	1/2	78	150	0-125	125	Manual	Polyurethane w/guard	3.8	8 1/16	4 23/64	
TA733	1/2	78	250	0-125	150	Manual	Zinc	3.8	8 1/16	4 23/64	
STANDARD DUTY MODULAR DESIGN, 5-MICROMETRES FILTRATION											
TA735	1/2	110	150	0-125*	125	Manual	Polyurethane w/guard	8.5	10 21/64	5 3/8	
TA736	1/2	110	150	0-125*	125	Auto	Polyurethane w/guard	8.5	10 21/64	5 3/8	
TA739	3/4	125	150	0-125*	125	Manual	Polyurethane w/guard	8.5	10 21/64	6 1/16	
TA740	3/4	125	150	0-125*	125	Auto	Polyurethane w/guard	8.5	10 21/64	6 1/16	

*Also available 0-25 PSI, 0-60 PSI, 0-250 PSI



Regulators (Gauge Included)

- High performance
- Compact design allows for greater design flexibility
- **Heavy-Duty:** High-capacity performance featuring rugged design for the most demanding applications

TOPRING

Model No.	NPT Size"	Max SCFM @ 100 PSI	Max PSI	Reduced Pressure Range PSI	Max Temp. °F	Bowl Type	H"	W"	Price /Each
HEAVY-DUTY									
BT861	3/4	300	300	5-250	125	Zinc	10 1/32	4 11/16	
TA670	1	400	300	0-125	125	Zinc	10 7/16	4 11/16	
TA672	1 1/2	500	300	0-125	125	Zinc	10 11/32	4 15/16	



Lubricators

- High performance over a wide flow range
- Easy maintenance
- Compact size

Model No.	NPT Size"	Max SCFM @ 100 PSI	Max PSI	Max Temp. °F	Bowl Type	Bowl Cap. oz.	H"	W"	Price /Each
COMPACT MODULAR DESIGN									
TA677	1/4	15	150	125	Polyurethane w/guard	3.8	6 15/16	2 3/16	
TA679	3/8	80	150	125	Polyurethane w/guard	3.8	6 15/16	2 3/16	
TA681	1/2	80	150	125	Polyurethane w/guard	3.8	6 15/16	2 3/16	
STANDARD DUTY MODULAR DESIGN									
TA683	1/2	110	150	125	Polyurethane w/guard	8.5	8 9/16	2 11/16	
TA684	1/2	110	250	150	Zinc	8.5	8 9/16	2 11/16	
TA685	3/4	125	150	125	Polyurethane w/guard	8.5	8 9/16	3 1/32	
TA686	3/4	125	250	150	Zinc	8.5	8 9/16	3 1/32	

