



CONCRETE TYPE 27

- High performance grinding and cutting
- These wheels for use on portable angle grinders have multiple high strength reinforcement and a matched super tough bond for extra safety in tough grinding and cutting applications
- They are made for fast material removal and smooth grinding and cutting of concrete, masonry, stone and similar building materials
- **1/8" Thick:** Fast and free cutting; formulated for cutting but may also be used for intermittent light grinding
- **1/4" Thick:** Excellent control in demanding applications; extra hard silicon carbide grain for fast material removal and long wheel life



Model No.	Mfg. No.	D"	x	Size T"	x	A"	Grade	Max RPM	Price /Each
UE693	08-D-452	4 1/2	x	1/8	x	7/8	C-24	13 300	
UE694	08-D-502	5	x	1/8	x	7/8	C-24	12 200	
UE696	08-D-702	7	x	1/8	x	7/8	C-24	8 600	
UE698	08-E-450	4 1/2	x	1/4	x	7/8	C-24	13 300	
UE699	08-E-500	5	x	1/4	x	7/8	C-24	12 200	
UE701	08-E-700	7	x	1/4	x	7/8	C-24	8 600	

BLUEFIRE DEPRESSED CENTER WHEELS

- Upgraded zirconia alumina grain chemistry and shape, blended with premium aluminum oxide grain provides 2-3 times the life of aluminum oxide wheel.
- Broad utility: from light to heavy pressure applications, on a wide range of materials: stainless steel, carbon steel and alloys, to grey iron
- Excellent performance-to-price ratio lowers total grinding costs
- Will not contaminate stainless steel



Model No.	Mfg. No.	D"	x	Size T"	x	A"	Max RPM	Price /Each
FOR CUTTING/NOTCHING & LIGHT GRINDING								
NR989	66252843190	4 1/2	x	1/8	x	7/8	13 580	
NO027	66252843194	5	x	1/8	x	7/8	12 225	
NO030	66252843198	6	x	1/8	x	7/8	10 185	
FOR GRINDING								
NR978	66252843192	4 1/2	x	1/4	x	7/8	13 580	
NO004	66252843188	9	x	1/4	x	7/8	6 600	

FLEXCUT™ TYPE 27

- Premium performance flexible grinding wheel especially formulated to deliver superior performance on all ferrous and non-ferrous metals
- Deep Diamond-Cut™ pattern and optimized formulation
- More flexibility
- Best handling on flat and curved surfaces
- Cooler grinding
- Better stock removal in all materials (steel, stainless steel, aluminum)
- 4 1/2" and 5" Flexcut™ flexible grinding wheels with the unique Spin-on quick change mounting system for better comfort and maximum productivity
- Always use flange model **UG580**



Model No.	Mfg. No.	D"	x	Size A"	Grade	Max RPM	Price /Each
VV411	15-L-453	4 1/2	x	5/8"-11	A-36-X-FLEX	13 300	
VV412	15-L-456	4 1/2	x	5/8"-11	A-60-X-FLEX	13 300	
VV413	15-L-460	4 1/2	x	5/8"-11	A-100-X-FLEX	13 300	
VV414	15-L-503	5	x	5/8"-11	A-36-X-FLEX	12 200	
VV415	15-L-506	5	x	5/8"-11	A-60-X-FLEX	12 200	
VV416	15-L-510	5	x	5/8"-11	A-100-X-FLEX	12 200	
UG128	15-L-602	6	x	5/8"-11	A-24-X-FLEX	10 200	
UG129	15-L-603	6	x	5/8"-11	A-36-X-FLEX	10 200	
UG130	15-L-606	6	x	5/8"-11	A-60-X-FLEX	10 200	
VV139	15-L-702	7	x	7/8"	A-24-X-FLEX	8 600	
VV140	15-L-703	7	x	7/8"	A-36-X-FLEX	8 600	
VV141	15-L-706	7	x	7/8"	A-60-X-FLEX	8 600	

D x T x A: Diameter x Thickness x Arbor Size
 D x A: Diameter x Arbor Size

The More You Buy,
 The More You **SAVE**
 Just ask us!

