



## Detex® Food Grade Machine Oil

- Versatile lubricant eliminates sticking, binding, and squeaking
- NSF H1 lubricant can be used anywhere within a facility where incidental food contact may occur
- Oily film penetrates to loosen frozen nuts and bolts
- Colourless formula will not stain product or equipment
- Safe on all metal surfaces
- Metal and X-ray detectable packaging
- Accepted for use in Canadian food processing facilities



| Model No. | Mfg. No. | Size  | Price /Each |
|-----------|----------|-------|-------------|
| AH209     | C01316   | 312 g |             |

## LU700 Food Grade Machinery Oil

- Economical, general-purpose lubricant
- Penetrates and loosens rust, dirt, scale and corrosion
- Non-silicone formula is excellent for use in areas where silicone overspray might interfere with carton sealing or capping operations
- Virtually odourless, tasteless and colourless
- For bottle and carton filling machinery, valves, pistons, rollers, stainless steel pumps, chain drive belts, paste and sauce fillers, cams on rotary-type fillers, mixers, conveyors
- NSF registered category code H1



| Model No. | Mfg. No.  | Size   | Price /Each |
|-----------|-----------|--------|-------------|
| AA139     | SC0700000 | 10 oz. |             |

## ChainMate® Chain & Wire Rope Lubricant

- Effective under extreme temperature and pressure ranges
- Fortified with molybdenum disulfide
- Deep penetration to the core of wire ropes
- High adhesion
- Lubricant and corrosion protectant
- Use with guards in place to eliminate costly down time
- Increases chain and wire rope life
- Reduces wear caused by friction and corrosion



| Model No. | Mfg. No. | Size   | Price /Each |
|-----------|----------|--------|-------------|
| AA877     | C02416   | 11 oz. |             |

## LU202 Moly Chain Lubricant

- Foaming action penetrates close tolerances of chain drive bushings and pins
- Specially formulated for all chain drive equipment
- Reduces wear, increases chain life up to three times when applied regularly
- Moly additive assures lubrication under extreme pressure
- Effective from -20°F to 300°F
- Excellent as a protective coating for stored metal parts
- For chain drives and pins, forklift trucks, tractors, machinery, workstand rollers, conveyors, motorcycle and bicycle chains, sprockets, clippers, cutter bars, chain saws, link and roller assemblies
- NSF registered category code H2



| Model No. | Mfg. No.  | Size   | Price /Each |
|-----------|-----------|--------|-------------|
| AA106     | SC0202000 | 11 oz. |             |

## Dry Film PTFE Lubricant

- Ideal for releasing moulded parts
- Excellent for high temperature applications up to 500°F (260°C)
- Dry, thin film won't attract dust or dirt
- Non-flammable
- No silicone or chlorinated solvents
- Safe on most surfaces



| Model No. | Mfg. No. | Size   | Price /Each |
|-----------|----------|--------|-------------|
| AA870     | C02616   | 11 oz. |             |

## Dry Lube PTFE Spray

- Lubricates and provides superior long-lasting corrosion protection with no oily residue
- Reduces friction and wear on blades and bits, door and window tracks, slides, conveyor belts, rollers, hinges, power tools and equipment
- Won't attract dirt, dust or oil
- Container Type: Aerosol Can
- Film Type: Dry



| Model No. | Mfg. No. | Size  | Price /Each |
|-----------|----------|-------|-------------|
| AF175     | 2209     | 284 g |             |

## 3-36® Multi-Purpose Lubricant

- NSF Category Code: H2
- Multi-purpose lubricant that also serves as a penetrant and corrosion inhibitor
- Leaves a clear, thin and long-lasting film



| Model No. | Mfg. No. | Size  | Price /Each |
|-----------|----------|-------|-------------|
| YA180     | 73005    | 311 g |             |

## Chain & Wire Rope Lubricant

- NSF Category Code: H2
- Blend of synthetic lubricants that penetrate deep and leave a tough protective film
- Extends the working life of chains and wire rope
- Reduces wear caused by corrosion and friction



| Model No. | Mfg. No. | Size  | Price /Each |
|-----------|----------|-------|-------------|
| MLN961    | 73050    | 283 g |             |

## Extreme Duty Open Gear Lube

- Recommended for reducing friction and wear in harsh environments
- Resists to heat and pressure



| Model No. | Mfg. No. | Size  | Price /Each |
|-----------|----------|-------|-------------|
| AF267     | 73058    | 340 g |             |