



Extend® Rust Treatments

- Goes on white and converts rust to a durable, black, metal-protective coating in 10 minutes
- Wirebrush parts and apply with brush or spray
- Surface rust must be present
- Use as a primer or finish coat
- Resists temperatures to 250°F intermittent, 200°F continuous
- Approved by the American Bureau of Shipping



LOCTITE

Model No.	Mfg. No.	Size	Price /Each
AA633	234981	1 qt.	
AA634	160802	1 gal.	
AC110	234984	5 gal.	

WD-40® Specialist™ Rust Release Penetrant

- Penetrates deep into crevices, threads and seams to break the bonds that hold stuck parts together
- Ideal for use on nuts, bolts, threads and locks
- Leaves behind a protective layer and helps prevent rust and corrosion from re-forming
- Quickly goes to work on rusted nuts, bolts, threads, locks and chains



SPECIALIST

Model No.	Mfg. No.	Format	Price /Each
AF171	01078	311 g	

Fixmaster® Steel Putty

- Steel filled, non-sagging, two-part epoxy that cures to a metal-like finish for rebuilding or repairing metal parts
- 0.3 sq.ft. coverage, at 1/4" thickness
- 225°F maximum operating temperature
- 4900 PSI tensile strength
- 30 minutes working time
- Functional cure in 6 hours
- Accepted for use in Canadian food processing facilities
- Colour: Grey



LOCTITE

Model No.	Mfg. No.	Size	Price /Each
AC341	219292	1 lb. kit	

Zinc Mate™

- Flashpoint: -19°C
- Fast evaporation rate
- Working Temperature: 54.4°C (Continuous) and 65.6°C (Intermittent)
- High performance coating of >93% pure zinc that electrochemically bonds with ferrous metals to form a galvanic cell
- Actively fights rust and corrosion
- Use as a touch-up for damaged galvanized coatings



Model No.	Mfg. No.	Size	Price /Each
YA185	73054	369 g	

SP-400™ Corrosion Inhibitor

- Long-term indoor/outdoor corrosion inhibitor that provides protection of all equipment subject to heat, humidity, chemicals or severely corrosive atmospheres
- Ideal on machined surfaces and assemblies subjected to long periods of storage
- NSF Registered H2



Model No.	Mfg. No.	Size	Price /Each
AF108	73282	284 g	

Fixmaster® Aluminum Putty

- Rebuilds and repairs aluminum equipment, forming a non-rusting finish
- 0.5 sq.ft. coverage, at 1/4" thickness
- 225°F maximum operating temperature
- 4000 PSI tensile strength
- 20 minutes working time
- Functional cure in 6 hours
- Accepted for use in Canadian food processing facilities
- Colour: Aluminum



LOCTITE

Model No.	Mfg. No.	Size	Price /Each
AC334	235615	1 lb. kit	

Bio-Rust Neutral pH Rust Removers

- Removes rust and other metallic particles
- VOC free, solvent free, non-flammable, pH neutral solution biodegradable
- Not controlled under WHMIS
- Non-corrosive rust remover
- High workload - can remove 1.5 kg (3.3 lbs.) of iron oxide per 20 L
- For use with iron and mild steel
- Deeply rusted parts may require longer soaking time
- After application of Bio-Rust, rinse parts in water to remove loosened contaminants
- After removing rust, dip pack into fresh bath or Bio-Rust to provide short term corrosion protection
- It is recommended to degrease part before using Bio-Rust
- Bio-Rust is designed for immersion applications only
- Immerse parts in Bio-Rust at room temperature and let react for at least 30 minutes



Cold Galvanised Corrosion Inhibitors

- 95% zinc-rich galvanised coating
- Commonly used as a flash rust preventative on welded areas
- Works like a hot-dip on ferrous metals indoors and out
- Three-year protection
- Withstands water temperature up to 212°F (100°C) and continuous dry heat up to 750°F (400°C)
- Flexible coating will not yellow, chalk, crack or peel
- Electrochemically protect bare metal
- Meets or exceeds these specs: MIL-P-46105 Weld Through Primer, Passes Preece Test for Hot-Dip Galvanizing



Model No.	Mfg. No.	Size	Price /Each
AA807	C00516	14-oz.	
AB552	C05128	1 gal.	

Fixmaster® Stainless Steel Putty

- Forms a non-rusting, very hard, durable finish on damaged stainless steel surfaces
- 0.25 sq.ft. coverage, at 1/4" thickness
- 225°F maximum operating temperature
- 4600 PSI tensile strength
- 20 minutes working time
- Functional cure in 6 hours
- Accepted for use in Canadian food processing facilities
- Colour: Grey



LOCTITE

Model No.	Mfg. No.	Size	Price /Each
AC332	235613	1 lb. kit	