



Electrode Holders

- Grip the electrode closer to the end
- Allows you to use 20% more of the electrode than with standard tong holders
- Manufactured from copper alloy for maximum conductivity and strength
- Fibreglass insulators are designed to withstand intense heat and impact
- Will not burn, break or carbon char
- Electrode Capacity: 3/32" (2 mm) - 3/16" (5 mm)



Model No.	Amps	Description	Price /Each
NT629	400	Electrode Holder w/Neck Ring	
NT631	600	Electrode Holder w/Neck Ring	
NT630	400	Slimline – Bernard® Style Holder	
NT818	-	Replacement Head for 400 Amps Electrode Holder	
TTV098	-	Replacement Head for 600 Amps Electrode Holder	



Bernard® Shortstub™ Electrode Holders

- Electrode can be used to within one inch of Shortstub™ head
- Built to last with a proven high impact, high heat separate head
- 2000-lb. gripping pressure
- Better visibility, greater hand-to-arc distance



Model No.	Mfg. No.	Amps	Electrode Capacity"	Price /Each
360-9001	40S	400	1/16 - 1/4	



Cam Action Cable Connectors

- One model fits cable sizes 4 through 4/0
- Manufactured from heavy wall precision machined brass alloy
- Cable is held securely by large dome screw
- Brass body assembly slides easily into unique heavy-duty neoprene insulator with no external screws to avoid shock hazards
- Cam locking connectors are compatible with most common brands



Model No.	Description	Price /Each
NT664	Male/Female Connector Set	
NT649	Male Half with Insulator	
NT650	Female Half with Insulator	

Either-End Cable Connectors

- For use with 1/0 - 2/0 cable
- Unique "Either-End" design allows ends to interlock without the need for male/female connection points
- Brass body assembly slides into heavy-duty neoprene insulator



Model No.	Mfg. No.	Description	Price /Each
NP528	E-102M	Either-End Connector Set	



Hammer-On Lugs

- Manufactured from heavy wall cast copper alloy, annealed for maximum conductivity
- Fast, easy installation, just slide into cable and strike it with hammer for durable connection



Model No.	For AWG Cable Sizes	Price /Each
NT606	1 - 4	
NT605	1/0 - 2/0	
NT604	3/0 - 4/0	

Dual Power Plugs

- Tough thermoplastic shell for long life
- Each dual combination plug is supplied with 30A blades and a flat 50A blade
- Built-in rejection feature prevents closure if blades are incorrectly positioned
- Shell and bottom are hinged in front for ease of assembly
- Solid brass blades with colour-coded terminals help to simplify wiring
- Nema Configuration: 6-30P/6-50P
- AC Voltage: 250 V
- Cord Diameter: 0.63" - 1.05"



Model No.	Mfg. No.	Description	Price /Each
XH645	931	Plug	

Solder/Crimp Lugs

- Manufactured from heavy wall copper alloy, annealed for maximum conductivity
- Long length and flared ends make installation fast and easy



Model No.	For AWG Cable Sizes	Price /Each
PB131	3/0 - 4/0	