



## Dial Torque Wrench

- Large easy-to-read dial
- Fast, accurate and easy to set in any industrial workplace
- Accuracy:  $\pm 3\%$  CW  $\pm 4\%$  CCW
- Includes custom molded plastic case



Model No.	Mfg. No.	Capacity		Increments		Drive Type"	Overall Length"	Price /Each
NKE124	DIN75B	0-75 in.-lbs.	0-9 Nm	5 in.-lbs.	0.25 Nm	1/4 Square	10.5	
NKE123	DIN250B	0-250 in.-lbs.	0-30 Nm	5 in.-lbs.	0.50 Nm	3/8 Square	10.5	
NJI147	DIN600B	0-600 in.-lbs.	0-70 Nm	10 in.-lbs.	2.0 Nm	3/8 Square	10.5	

## Dial Torque Wrench with Memory Needle


- Large easy-to-read dial
- Fast, accurate and easy to set in any industrial workplace
- Accuracy:  $\pm 3\%$  CW  $\pm 4\%$  CCW
- Includes custom molded plastic case



Model No.	Mfg. No.	Capacity		Increments		Drive Type"	Overall Length"	Price /Each
QP111	DFN50B	0-50 ft.-lbs.	0-70 Nm	1 ft.-lbs.	2 Nm	3/8 Square	10.5	
NJI146	DFN250B	0-250 ft.-lbs.	0-350 Nm	5 ft.-lbs.	10 Nm	1/2 Square	21.5	

## Heavy-Duty Micro-Adjustable Torque Wrench

- Power Source: AC
- Type of Bulb: LED
- Measurement System: Metric
- Rugged metal knurled handles
- Quick-release button for faster socket retention and removal
- Can be trusted in any automotive, aircraft, marine and industrial applications
- Operates and ratchets in both left and right hand directions
- Includes custom molded plastic case



Model No.	Mfg. No.	Drive Type"	Capacity		Increments		Overall Length"	Head Style	Price /Each
NJH064	81250	1/4 Square	30-250 in.-lbs.	4-28.8 Nm	1 in.-lbs.	0.11 Nm	12 1/2	Fixed	
NJH066	82250	3/8 Square	30-250 in.-lbs.	4-28.8 Nm	1 in.-lbs.	0.11 Nm	12 1/2	Fixed	
TYW979	MFR80FL	3/8 Square	10-80 ft.-lbs.	13.5 - 108.5 Nm	0.5 ft.-lbs.	1.4 Nm	16 1/2	Flex	
NJH065	82100	3/8 Square	10-100 in.-lbs.	23.7-139 Nm	0.5 ft.-lbs.	0.7 Nm	17	Fixed	
NJH070	83250	1/2 Square	30-250 in.-lbs.	47.5-345.8 Nm	1 ft.-lbs.	1.4 Nm	22	Fixed	
TY272	MFR250H	1/2 Square	30-250 in.-lbs.	47-332 Nm	1 ft.-lbs.	1.4 Nm	24 1/4	Fixed	
NJH075	84600	3/4 Square	100-600 in.-lbs.	169-847 Nm	5 ft.-lbs.	7.0 Nm	46	Fixed	
TY273	MFR600H	3/4 Square	100-600 in.-lbs.	169-779 Nm	5 ft.-lbs.	6.8 Nm	43	Fixed	
TYR634	MF2000	1 Square	300-2000 ft.-lbs.	474-2700 Nm	10 ft.-lbs.	13.5 Nm	109	Fixed	

## Torque Multiplier

- Accuracy:  $\pm 5\%$



Model No.	Mfg. No.	Max Input Torque		Max Output Torque		Input Drive"	Output Drive"	Weight With Case	Price /Each
		ft. lbs.	Nm	ft. lbs.	Nm				
TYR665	TM750A	227	303	750	1017	1/2 F	3/4 M	4 lbs.	
TYR662	TM1200	200	271	1200	1627	1/2 F	3/4 M	12.5 lbs.	
TYR663	TM2200	162	271	2200	2983	1/2 F	1 M	15.2 lbs.	
TYR664	TM3200	173	235	3200	4339	1/2 F	1 M	19.9 lbs.	

## Beam Torque Wrench

- Scale includes both SAE (In/Lb, Ft/Lb) and Metric (Nm)
- Serviceable by bending pointer to zero before use
- Palm-fit handle pivots on beam to maintain constant distance from drive point to load point for precise measurement
- Directly measure a variety of torque values when tightening fasteners
- Pointer moves clockwise or counter-clockwise ( $\pm 7\%$ ) to measure torque



Model No.	Mfg. No.	Overall Length"	Drive Type"	Torque Range	Increments	Tool Weight lbs.	Price /Each
TDS979	2955D	11	1/4 Square	0-60 in.-lbs.	2.5 in.-lbs.	0.85	
TDS941	2956D	16	3/8 Square	0-600 in.-lbs.	50 in.-lbs.	1.45	
TDS949	2957N	20	1/2 Square	0-150 ft.-lbs.	5 ft.-lbs.	1.89	