

Polyester Cord Strapping

- Tougher, stronger, and safer than polypropylene strapping
- Will not scratch or mar delicate surfaces
- Available in Uniline bonded cord strapping and crosswoven cord strapping
- Uniline cord is manufactured by bonding fibres together and is easy to tie
- Crosswoven cord strapping has a
- cross weave added between the fibres Crosswoven strapping will not split or fray
- Used only in manual applications
- Polyester cord strapping offers excellent resistance to moisture
- Frequently used in outdoor applications
- Heavy-duty polyester sizes are frequently used in lumber applications, agricultural and boat industries

Strap









INDUSTRIAL WIRE BUCKLES 3/4", 1000/box

Model No. PB908 Price/Each \$



DISPENSER Model No. PB753 Price/Each \$



Bonded	Woven	Width"	lbs.	/Coil	Bonded Woven
PB017	PB018	1/4	300	7800	
PB019	PB020	3/8	450	5250	
PB021	PB022	1/2	600	3900	
PB023	PB024	5/8	725	3000	
PB025	PB026	3/4	900	2100	

Polyester Strapping

- Ideal for medium to heavy-duty palletizing
- Moisture-resistant, safe to handle and recyclable
- Approved by the Association of American Railroads (AAR)
- Grade: Manual





Model	Strap	Strength	Feet		Strap	Core	Price
No.	Width"	lbs.	/Coil	Colour	Thickness"	Dimensions	/Each
PG557	5/8	1100	1800	Black	0.03	16" x 3"	
PG555	1/2	770	2756	Black	0.025	16" x 3"	
PG556	1/2	820	3250	Black	0.028	16" x 3"	
PG554	1/2	600	3380	Green	0.02	16" x 3"	
PG561	5/8	1400	3500	Green	0.04	16" x 6"	
PG175	5/8	1400	4000	Green	0.035	16" x 6"	
PG560	3/4	1800	2680	Green	0.04	16" x 6"	
PG559	1/2	770	5800	Black	0.025	16" x 6"	
PG558	1/2	820	6315	Green	0.028	16" x 6"	

Polypropylene Strapping Sealers

- Heat treated steel construction for superior strength and durability
- Prevents strapping from loosening during transit
- Long 18" handle requires less effort
- · Use on open steel seals

PA555

PA556

PF459



L.			
Strap Thickness"	Price /Each		
≤ 0.027 0.023 - 0.039			

KLETON

< 0.027

Polypropylene & **Polyester Strapping Tensioners**

1/2

5/8

- Ideal for applications on flat surfaces
- Accepts strapping 3/8 -3/4" wide and up to 0.035" thick
- Superior design and performance
- Premium copper bushings Built-in strapping cutter
- Model No. PC939 Price/Each \$



Serrated Strapping Seals

Serrated seals for use with polyester strapping



			Pricea per Box		
Model		Fits Strap	Qty	Price	
No.	Type	Width"	/Box	/Each	
PF991	0pen	5/8	1000		
PG577	0pen	3/4	1000		
PG576	Open .	1/2	1000		

Polyester Strapping Tensioners

- Tightens strapping quickly with little effort
- Built-in strapping cutter
- Ideal for applications on flat surfaces
- Compatible with polyester strapping
- Fits Strap Width: 3/8" 3/4"
 Fits strapping thickness: 0.023" to 0.039"

Model No. PF993 Price/Each \$



Polyester Strapping Sealers

- Heat-treated steel construction for superior strength and durability
- Prevents strapping from loosening during transit
- Long 18" handle requires less effort
- Offset jaws are longer on one side for better grip
- Specially designed for use with serrated seals

Model No. PF992 Price/Each \$



