



## Heavy-Duty 2-Ton Tripod-Style Underhoist Component Stand

- Adjusts from 55" to 85-1/2"
- Ideal for exhaust and suspension work
- Bearing included for smooth operation
- Easily dismantles for storage
- Not designed to support entire vehicle but may be used to stabilize vehicles that are raised by in ground or above ground lifts
- Dimensions: 46-1/2" x 8-2/3" x 3"

**Model No. UAV886**  
**Mfg. No. 032202**  
**Price/Each \$**



## Single-Acting Hand Pump

- Single acting hand pumps made of high strength alloy steel; corrosion resistant and engineered for use in extreme environments
- Internal pressure relief valve for overload protection
- Compact design for storage and transportation
- Compatible with various cylinders and tools
- Operation Type: Manual Hydraulic
- Handle Force: 108 lbs.
- Oil Output per Stroke - 1st Stage: 2.038 in<sup>3</sup>
- Oil Output per Stroke - 2nd Stage: 0.201 in<sup>3</sup>
- Oil Output Thread: 3/8"-18NPT
- Pressure Rating - 1st Stage: 360 PSI
- Pressure Rating - 2nd Stage: 10 000 PSI
- Weight: 16.06 lbs.
- Usable Oil Volume: 55 in<sup>3</sup>

**Model No. UAV891**  
**Mfg. No. 033101**  
**Price/Each \$**



## Truck Jack

- Designed for heavy duty truck and trailer shop use
- Fully welded hydraulic pump and cylinder construction
- Two-piece 42.7" handle
- Operates at 90 ~ 145 PSI
- Standard accessories: 3 piece adapter kit including 3/4", 2-1/2", and 4" extensions
- Lifting Capacity: 22 Ton(s)
- Lowered Height: 9"
- Raised Height: 13-1/2"
- Operation Type: Air Hydraulic

**Model No. UAV882**  
**Mfg. No. 030670**  
**Price/Each \$**



## Super Heavy-Duty Bottle Jack

- Built tough for the rigors of the heavy duty trucking, agricultural and fleet business
- Operating pressure 110-120 PSI
- Dual return springs for faster ram retraction
- Safeties bypass system
- Reinforced base for added stability
- Precision machining reduces O ring damage
- Superior quality O rings for longer life and greater seal
- Premium components provide for a 4 to 1 greater life expectancy
- Manual function allows for normal operation anywhere, even without an air supply
- Lifting Capacity: 20 Ton(s)
- Lowered Height: 10-1/3"
- Raised Height: 20"
- Operation Type: Air Hydraulic
- Lift: 6.3"
- Screw Extension: 3.3"

**Model No. UAV863**  
**Mfg. No. 030158**  
**Price/Each \$**



## Low Profile Transmission Jack

- Ideal for handling medium to heavy weight truck transmissions
- Low profile design enables access to the lowest clearance trucks
- Wide chassis provides efficient load distribution and increased stability
- 4-Way tilting head allows the user to easily position the jack for installation and removal of the transmission
- Fully adjustable universal saddle with adjustable arms to position the transmission securely
- Full 360° rotating handle for use in any position
- Lifting Capacity: 1 Ton(s)
- Lowered Height: 11-9/10"
- Raised Height: 30-1/2"
- Backward Tilt: 10°
- Forward Tilt: 15°
- Base Dimensions: 36-6/10" x 22-3/4"

**Model No. UAV880**  
**Mfg. No. 030546**  
**Price/Each \$**



## High Lift Professional 2-Stage Transmission Jack

- STRONGARM Hydraulic Telescopic Transmission Jacks provide service technicians one-man capabilities for installing transmissions, differentials or transfer case
- Telescopic two-stage hydraulics for greater lift range, precise load control and rapid lift
- Convenient foot-operated pump allows mechanic to use both hands to position and align saddle with transmission
- Fully adjustable universal saddle with hand adjustable corner brackets and safety chain
- Wide base with four swivel caster wheels for easier, more efficient under-hoist positioning
- Safety overload system prevents jack from being used beyond the ASME/PASE load-limiting standard
- Meets ASME 2014 Standards
- Lifting Capacity: 1 Ton(s)
- Lowered Height: 37"
- Raised Height: 76-3/8"
- First Stage: 19-3/8"
- Second Stage: 20"
- Weight: 173.06 lbs.

**Model No. UAV879**  
**Mfg. No. 030537**  
**Price/Each \$**



## Heavy-Duty Jack Stand

- Efficient pin-type post with four height adjustment positions
- Large 3" x 3-7/8" saddle
- 10" x 10" square base secures and stabilizes load
- Meets ANSI standards for performance and safety
- Balanced carry handle
- Capacity: 22 Ton(s)
- Lowered Height: 13-3/4"
- Raised Height: 19-3/4"
- Lock Type: Locking Pin

**Specs**  
**Model No. UAV888**  
**Mfg. No. 032230**  
**Price/Each \$**

