



# EXTENSION CORDS

## Outdoor Vinyl Extension Cords

- Designed for industrial and contractor use
- Vinyl jacket protects against rough use, chemicals, and moisture and provides added flexibility
- Molded-on and bonded plugs and connectors resist breaking



### 3-CONDUCTOR SJTW, 300 V GROUNDING

Model No.	Length'	AWG	Amps	Watts	Colour	Price /Each
<b>HEAVY-DUTY</b>						
XC482	25	14/3	15	1875	Orange	
XC483	50	14/3	15	1875	Orange	
XC484	100	14/3	13	1625	Orange	
<b>EXTRA HEAVY-DUTY</b>						
XC485	25	12/3	15	1875	Yellow	
XC486	50	12/3	15	1875	Yellow	
XC487	100	12/3	15	1875	Yellow	

XC485



NEMA 5-15P



NEMA 5-15R

## Outdoor Vinyl Triple Tap Extension Cords

- Designed for industrial and contractor use
- Vinyl jacket protects against rough use, chemicals, and moisture
- Vinyl jacket provides added flexibility
- Molded-on and bonded plugs and connectors resist breaking



### 3-CONDUCTOR SJTW, 300 V GROUNDING

Model No.	Length'	AWG	Amps	Watts	Colour	Price /Each
<b>HEAVY-DUTY</b>						
XC488	25	14/3	15	1875	Red	
XC489	50	14/3	15	1875	Red	
XC490	100	14/3	13	1625	Red	
<b>EXTRA HEAVY-DUTY</b>						
XC491	25	12/3	15	1875	Red	
XC492	50	12/3	15	1875	Red	
XC493	100	12/3	15	1875	Red	

XC491



NEMA 5-15P



NEMA 5-15R

## Outdoor Vinyl Triple Tap Extension Cords

- Designed for use by contractors and industrial personnel
- Jacket protects against rough use, chemicals, moisture, ozone and gives added flexibility at below freezing temperatures
- Molded-on and bonded vinyl plugs and connectors resist breaking or pulling off cord
- Nickel-coated brass blades resist corrosion
- **XA719, XA720, XA721** are No Overload® circuit breaker extension cords



### 3-CONDUCTOR SJTW, 300 V GROUNDING

Model No.	Length'	AWG	Amps	Watts	Colour	Price /Each
<b>HEAVY-DUTY</b>						
XA719	25	14/3	15	1875	Red	
XA720	50	14/3	15	1875	Red	
XA721	100	14/3	13	1625	Red	
<b>EXTRA HEAVY-DUTY</b>						
XA722	25	12/3	15	1875	Yellow	
XA723	50	12/3	15	1875	Yellow	
XA724	100	12/3	15	1875	Yellow	

XA719



NEMA 5-15P



NEMA 5-15R

## Glacier Flex™ 3-Outlet Engine Block Heater Cords

- 3 conductors, SJTW -50°C, 300 V grounding
- Water-resistant
- Flame retardant
- Ultra flexible
- Nickel-coated brass blades resist corrosion
- Temperature range from -50°F to +140°F (-50°C up to +60°C)
- Primalight® indicator light flashes blue and red when power is on



Model No.	Length'	AWG	Amps	Watts	Price /Each
XC730	15	16/3	13	1625	

XC730

